

SOLIDEAL PON 775

BY CAMSO



PRESS-ON
TIRES



DESIGNED FOR HIGH INTENSITY APPLICATIONS

Engineered to provide the best performance of heat resistance, energy efficiency and long-lasting life in high intensity applications.

PERFORMANCE

INTENSITY



ENERGY SAVINGS



TIRE LIFE



camsso.co



FORMERLY
CAMOPLAST
SOLIDEAL

PRESS-ON TIRES

SOLIDEAL PON 775

BY CAMSO

TIRE SIZE ⁽¹⁾	TREAD	ACTUAL TIRE DIMENSIONS			LOAD CAPACITY ⁽²⁾ Counterbalanced lift trucks (kg)					
	SMOOTH PON 775	OVERALL DIAMETER (mm)	OVERALL WIDTH (mm)	REPLACEMENT OVERALL DIAMETER ⁽³⁾ (mm)	10 km/h		16 km/h		25 km/h	
					LOAD WHEEL	STEERING WHEEL	LOAD WHEEL	STEERING WHEEL	LOAD WHEEL	STEERING WHEEL
10 X 4 X 6 1/2	■	254	102	224	780	640	695	585	565	465
10 X 5 X 6 1/2	■	254	127	224	1010	830	905	760	735	605
10 1/2 X 5 X 6 1/2	■	267	127	232	1070	880	960	810	780	640
12 X 4 1/2 X 8	■	305	114	270	1040	855	930	780	755	620
13 1/2 X 5 1/2 X 8	■	344	140	296	1510	1240	1345	1130	1095	895
14 X 4 1/2 X 8	■	357	114	305	1170	960	1045	875	850	695
14 X 5 X 10	■	357	127	321	1335	1095	1195	1000	970	795
16 X 5 X 10 1/2	■	406	127	359	1510	1240	1345	1130	1095	895
16 X 6 X 10 1/2	■	406	152	359	1910	1570	1710	1435	1390	1140
16 X 7 X 10 1/2	■	406	178	359	2325	1910	2070	1740	1685	1380
15 X 5 X 11 1/4	■	381	127	348	1390	1140	1240	1040	1010	830
16 1/4 X 5 X 11 1/4	■	413	127	370	1530	1250	1360	1145	1105	905
16 1/4 X 6 X 11 1/4	■	413	152	370	1920	1580	1715	1440	1395	1140
16 1/4 X 7 X 11 1/4	■	413	178	370	2325	1900	2060	1735	1680	1380
18 X 6 X 12 1/8	■	457	152	407	2100	1720	1870	1575	1525	1250
18 X 7 X 12 1/8	■	457	178	407	2550	2100	2280	1910	1855	1520
18 X 8 X 12 1/8	■	457	203	407	3000	2475	2680	2250	2180	1790
21 X 7 X 15	■	533	178	481	2875	2350	2560	2150	2085	1710
21 X 8 X 15	■	533	203	481	3375	2775	3025	2540	2455	2015
21 X 9 X 15	■	533	229	481	3900	3200	3475	2920	2830	2320
22 X 8 X 16	■	559	203	507	3500	2875	3130	2625	2545	2085
22 X 9 X 16	■	559	229	507	4050	3325	3600	3025	2930	2400
22 X 10 X 16	■	559	254	507	4575	3750	4080	3425	3315	2720
22 X 12 X 16	■	559	305	507	5625	4625	5030	4225	4090	3350
28 X 12 X 22	■	710	305	658	6740	5540	6020	5060	4900	4015



WIDEST POSSIBLE FLAT FOOTPRINT

- Reduces ground pressure to minimize heat build-up

THERMALLY EFFICIENT CONSTRUCTION

- Provides a cooler running tire and the best in class energy efficiency

ABRASION-RESISTANT TREAD COMPOUND

- Increases tire life



UNIQUELY ENGINEERED SIDEWALL

- Reduces heat build-up caused by stresses in the tread shoulders

WEAR INDICATOR AND SAFETY LINE

- Indicates when you should replace your tire

AUTHORIZED DISTRIBUTOR:

Remarks

(1) Tolerances on wheel diameter • Code designated sizes (in): nominal rim diameter +0,005”/-0” • Metric sizes (mm): h11 according to ISO/R286. Surface roughness Ra < 6.3 µm • Chamfer 5 mm wide @ 30°

(2) The speeds quoted in the table are the maximum speeds of the unloaded vehicle. An increase in load capacity for lower speeds is not permitted.

(3) The tire is considered worn out when the outside diameter is equal or smaller than the replacement overall diameter.

It is possible that certain items are not sold in your region.

Please contact your local sales contact to check tire availability in your region.



Camso is the best of Camoplast and Solideal.
To keep moving forward while staying true to our history,
we're now the Road Free company.

camso.co



FORMERLY
CAMOPLAST
SOLIDEAL